

# INDIA'S MOST RELIABLE POULTRY AND LIVESTOCK FEED EQUIPEMENT













### COMPOSITE FEED MILL

Consists of Popular Hammer Mill having Magnet fitted to intake hopper, Screw Conveyor (Auger) and Horizontal Feed Mixer which make this combination e Semi-Automatic Feed Mill.

MO	DEL	RAN	IGE

Model	VA 1915 14	Power	
	Kgs./Batch	Capacity Shift 8 hrs.	0.0700.73
SEW (S)	250-300	6-8 Tons	12 H.P.
SEW (M)	500-750	12-15 Tons	22.5 H.P
SEW (B)	1000-1200	20-25 Tons	35-40 H.P.

Model SEA (B) Requires additional screw conveyor (Auger) and storage Bin above the Mixer.





### **POPULAR HAMMER MILL**

This Hammer Mill is Highly out put gravity flor mill. It comprises of two functions in one i.e. Grinding ans Grading. It gives cool grinding in one direct operations. The fineness of the grinding is adjust by chance of performed screen. Which can be done within minutes. The special features are:

#### MODEL RANGE

Model	Capacity Shift 8 hrs.	Power	
SEW-800	6-8 Tons	3 H.P.	
SEW-1000	12-14 Tons	7.5 H.P.	
SEW-2000	16-18 Tons	10 H.P.	
SEW-4000	28-30 Tons	20 H.P.	
SEW-8000	40-42 Tons	40 H.P.	

### TROPICAL HAMMER MILL

Fan type elevating Hammer mill for General use designed to Grind. Various types of materials, such as Maiz, Oil Cake, Small Grains, Cereals and Chemicals, It comprises of three functions in one.

(i) Grinding (ii) Grading (iii) Transporting and has optical double bagging cyclone. All models have swinging hardened hammers with high grinding efficiency.

#### MODEL RANGE

Model	Capacity Shift 8 hrs.	Power
SEW-400	4-6 Tons	5 H.P.
SEW-750	6-10 Tons	7.5 H.P
SEW-1000	12-16 Tons	10 H.P.
SEW-2500	20-24 Tons	20 H.P.





### DOUBLE DOOR HAMMER MILL

Double door hammer mill is full screen grinder having 80% screening area as compare to 50% of half screen grinder. This machine is of Latest Technology and best for fine or coarse grinding.


#### The Special Features are:

- \* Efficient Grinding
- \* Balanced Rotor
- \* Gap Adjustment
- \* Quick Spann-Locking Mechanisum
- \* Bidirectional Rotation
- \* Four Time Reversible Hardened.

and Shaped Beaters for Best grinding efficiency.

Complete range available of Double Door Hammer Mill from 5 H.P. for small users to 180 H.P. for big feed mills with Auto feeder and magnet systems.





### **PULVERISOR**

An Ideal mill to grind anything like (Spices, Haldi, Mirch, Chemicals) The Pulverising is done in mid air by hammers, unlike friction grinding in other grinding mills. The ground meal, therefore is (Clod and Retains its flavour). The meal is then sieved and pneumatically carried to the cyclone for convenient bagging.

MODEL RANGE

Model	Size	Capacity Shift 8 hrs.	Power
SEW-A	9" x 4"	5-6 Kg.	2 H.P.
SEW-B	13" x 5"	15-20 Kg.	3 H.P.
SEW-C	16" x 7"	45-50 Kg.	5 H.P.
SEW-D	18" x 8"	80-85 Kg.	10 H.P.
SEW-E	20" x 10"	200-225 Kg.	20 H.P.
SEW-F	21" x 12"	300-350 Kg.	30 H.P.
SEW-G	24" x 14"	400-425 Kg.	40 H.P.

### WHIRLWIND MIXER

These vertical type mixers are most ideal dry mixing. The Principal is not to stir or trumble but to whirl the ingredients the mixing chamber. Vertical screw Conveyor lifts the ingredients to top, where mixing paddles whirls particles to the wall of mixing chamber following to the bottom. This mix is lifted and whirled again & again to give homogen-ousmix. The biggest advantage of this type mixer is that both feeding and discharge are at ground level.

MODEL RANGE

	III O D III I	1. M. M. M. W. St.	
Model	Capacity Kgs./Batch Shift 8 hrs.		Power
SEW-S	100 Kg.	3-4 Tons	1 H.P.
SEW-A	300 Kg.	7-8 Tons	2 H.P.
SEW-B	500 Kg.	10-12 Tons	5 H.P.
SEW-C	1000 Kg.	16-18 Tons	7.5 H.P.
SEW-D	1400 Kg.	20-22 Tons	10 H.P.
SEW-E	1750 Kg.	25-28 Tons	12.5 H.P.





### HORIZONTAL FEED MIXERS

Horizontal mixers are most suitable for processing animal Feeds. i.e. for Poultry, Cattle pig, Sheeps and Aqua feeds. These mixers are real versatile machines. These produce a hom-ogenous mix of ingredients. Molasses, Liquids, Fats can be directly added. These mixers have the following features:

\* Designed for trouble free services


\* Unique Tumbling action giving good accurate Mixing.

\* Slow moving "soft mix" action eleminates product damage and degradation.

\* Within five minutes an excellant homogenous mix is prepared.

		NGE
	_ 110	

Model A1/A2	Size	MODELTO	Capacity	Power
model/ m/ iz		Kgs./Batch	Shift 8 hrs.	
SEW Junior	20 Cuft	250-300	8-10 Tons	5 H.P.
SEW Medium	50 Cuft	500-750	16-20 Tons	10 H.P
SEW Super	100 Cuft	1000-1200	22-30 Tons	15 H.P.
SEW Jumbo	200 Cuft	2000-2200	36-40 Tons	25-30 H.P.







### MINERAL MIXER

Available in 25 kg., 50 kg. and 100 kg. Models Mixing Chamber made out of 304 grade Stainless Steel. Machine Fitted with reduction gear box.

#### MODEL RANGE

Model	Capacity Shift 8 hrs.	Power
SEW 25	25 Kg.	1 H.P. Single Phase
SEW 50	50 Kg.	2 H.P. Single Phase
SEW 100	100 Kg.	3 H.P. Three Phases

### DOUBLE SHAFT PADDLE MIXER

- \* Gentle and evenly mixing; the density of filling material can be varied from 0.4-1
- \* High mixing speed, shot mixing cycle, 30-120S/Batch.

\* High uniformity; CV <3-5%

- \* Full length electric or pneumatic discharging door with quick discharging and low residue, Good sealing tightness, higher than national standard.
- \* Atomizing spaying system and air cleaning system is optional.

#### MODEL RANGE

111.00.00				
Model	Amount per Batch	Power		
SEW 1	100 Kg.	4 (5.5) KW		
SEW 2	250 Kg	5.5 (7.5) KW		
SEW 3	500 Kg.	11 (15) KW		
SEW 4	1000 Kg.	15 (18.5) KW		
SEW 5	2000 Kg.	30 (37) KW		
SEW 6	3000 Kg.	37 (45) KW		
SEW 7	4000 Kg.	45 (55) KW		






### HORIZONTAL PELLET MILL

Both types of Pellet Mills Viz Vertical as well as Horizontal are manufactures under strict supervision of engineers specilised in this field. These machines can meet all needs of any types of pellets for Poultry, Cattle, Pigs or Aqua Pellet Feed.

The heart of the pelleting machine is in the roller's/die's system which are made out of special alloy steel and are hardened to reduce the wear and tear.

#### MODEL RANGE

Model	Capacity with one die 3mm Qnt./hrs.	Powe	
SEW 1/2 SEW 1	8-10 Qnt.	30 H.P.	
SEW 2	10-15 Qnt. 20-25 Qnt.	50 H.P. 75 H.P.	
SEW 3	30-35 Qnt.	125 H.P.	



### **VERTICAL PELLET MILL**

M	$\sim$	n		E. C.	n	A	к.	~	r
IVI			_	100	PC.	м	n	1.9	-


Model	Capacity	Power	
N. W. Sameria	with one die 9mm x 18mm Kg./hrs.	30000000	
SEW-16"	350-500 Kg./hr.	30 H.P.	
SEW-20"	800-1000 Kg./hr.	50 H.P.	
SEW-26"	1300-1500 Kg./hr.	75 H.P.	
SEW-30"	1700-2000 Kg./hr.	100 H.P.	



DIES & ROLLS

Counterflow COOLER







Gyro Screen





### PET FOOD/FISH FOOD PROCESSING LINE



- 1. Mesh Plant
- 2. Twin/Single Screw Conveyor
- 3. Pneumatic conveyor
- 4. Drver

- 5. Elevator
- 6. Roller
- 7. Oil Sprayer









Model/ Parameter	SLG65-III Fish Food Processing line	SLG70-III Fish Food Processing line	SLG85-III Fish Food Processing line
Installed Capacity	70 KVA	120 KVA	145 KVA
Power	35 kw	75 kw	100 kw
Output	120-160 kg/h	220-260 kg/h	500-550 kg/h
Dimension	12 x 2 x 4m	33 x 2 x 4m	35 x 2 x 4m

### **SEW GRAIN FEEDER**



### SEW SCREW CONVEYOR



Note : Above Conveyor /Feeder are available in different capacities as required.



**Bucket Elevator** 



### PELLET PRESS WITH ELECTRIC MOTOR


#### MODEL RANGE

MODELIGATOR								
	Model	Size (in mm)	Capacity	NW/GW(kg	Power			
	SEWM200B	1000x430x950	200-300	200/300	3Phase 7.5 KW			
	SEWM230B	1140x470x970	300-400	290/320	3Phase 11 KW			
	SEWM260B	1200x500x1070	400-600	330/360	3Phase 15 KW			
	SEWM300B	1270x520x1070	700-800	410/450	3Phase 22 KW			
	SEWM360B	1270x520x1070		470/500	3Phase 22 KW			
	SEWM400B	1470x600x1150	900-1100	550/585	3Phase 30 KW			

### MESH PLANT

Capacity 1/2 ton to 10 ton

### BAGGING SYSTEM WITH STITCHING CONVEYOR



### **FEATURES**

Rugged, Reliable & Accurate High Speed and Accuracy 10 to 100kg Cloth/Jute/LDPE Bag Two Stage Filling Auto/Manual With 300kg Surge Hopper PC Connectivity

### FEEDING MECHANISM

Gravity Feed

Vibro Feed

Screw Feed & Belt Feed Depending on Material Flow

AVAILABLE IN TWO MODELS

6 Feet Model

12 Feet Model







## Poultry & Cattle feed Plant Capacity 1 Ton to 10 Ton



Latest Technology Manufactured on CNC Machines

Manufacturers & Exporters:

### SHAKTI ENGINEERING WORKS (REGD.)

G.T. ROAD, BATALA - 143505 (PUNJAB) INDIA

TELE .: +91 1871 243167, 223188 FAX : +91 1871 243149

Mobile No.: +91 98720-92939, +91 98765 41111, +91 98140-56453

E Mail: hitesh.infra@gmail.com Website: www.mggroupint.com